



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> :  A61J 3/07	A1	(11) International Publication Number: WO 94/09745 (43) International Publication Date: 11 May 1994 (11.05.94)
--	----	---

(21) International Application Number: PCT/GB93/02270

(22) International Filing Date: 4 November 1993 (04.11.93)

(30) Priority data:  
9223172.9 5 November 1992 (05.11.92) GB

(71) Applicant (for all designated States except US): R.P. SCHERER CORPORATION [US/US]; 2075 West Big Beaver Road, Troy, MI 48084 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): RASHID, Abdul [GB/GB]; 25 Camphill Avenue, Glasgow G41 3AU (GB). STEVENS, Howard, Norman, Ernest [GB/GB]; Ballyconachy, Balmaha Road, Drymen, Stirlingshire G63 0BX (GB). BAKHSHAEI, Massoud [IR/GB]; 8 Park Avenue, Glasgow G64 2SN (GB). KELSO, James, Robertson, Miller [GB/GB]; 24 Courthill Street, Dalry, Ayrshire KA24 5AN (GB). HEGARTY, Mark [GB/GB]; 34 Alwyn Drive, Stewartfield, East Kilbride G74 4RL (GB). MACKIE, James, Leonard [CA/CA]; 3350 Dolphin Court, Windsor, Ontario N8R 2G7 (CA).

(74) Agents: HORNER, Martin, Grenville et al.; Cruikshank &amp; Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).


(81) Designated States: AU, CA, JP, KR, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

**Published***With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: CAPSULE CONSTRUCTION

## (57) Abstract

A controlled release capsule comprises a male plug (2) formed of a water swellable hydrogel which is engaged within a neck portion (4) of a female body (6). The capsule contains a pharmaceutically active material. In contact with an aqueous medium, such as in the gastrointestinal tract, the hydrogel plug swells and becomes disengaged from the body, thereby releasing the active material. In order to facilitate insertion of the male plug into the neck of the body, the body has a flared mouth portion (14) which is wider than the neck. The neck itself may be wider or narrower than the remainder of the body. A water-soluble cap (8) has detentes (18) which clip over the flared mouth portion so as to lock the cap thereto.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TC	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

-1 -

CAPSULE CONSTRUCTIONTECHNICAL FIELD

The present invention relates to a controlled release capsule construction intended for containing a pharmaceutically active material, which comprises a male member engaged within a neck portion of a female body; the capsule including a water swellable material which swells so as to disengage the female body upon exposure of the capsule to an aqueous medium.

BACKGROUND

International Patent Specification WO 90/09168 discloses a device of this type which comprises a water swellable male plug engaged within a female body. A pharmaceutically active material is contained within the device. When the capsule is exposed to water, the male hydrogel plug swells and eventually disengages itself from the female body, thereby allowing the pharmaceutically active material contained within the device to be released. It has been found that the time taken to release the pharmaceutical material is predictable and reproducible, so that the device may be used to release pharmaceutically active materials within the body of a patient after a predetermined time interval (e.g. 0.5 to 12 hours). This may, for example, be useful in the treatment of medical conditions where it is desirable to

-2 -

administer a pharmaceutically active material to the patient sometime through the night, while the patient is asleep, so as to provide a desired level of the drug in the patient in accordance with his needs, for example during the night or when he awakes. It may also be useful to allow dosing of materials at a predetermined point as the capsule passes through the gastro-intestinal tract, for example in the colon.

Patent specification W092/13521 (Alza Corporation) describes fluid-imbibing dispensing devices for delayed delivery of an active agent, which include an expansion means which absorbs fluid from a surrounding environment. The dispensing device comprises a housing having first and second wall sections telescopically engaged with each other, particularly a capsule having a hollow cap and a hollow body; either the cap or the body is in the form of a male section fitted inside the open end of the other female section. The expansion means is contained within the device and expands as it absorbs fluid, forcing apart the two sections of the device. The expansion means may be a swellable polymer or an osmotic formulation which swells as it absorbs fluid. In order to allow fluid to come into contact with the expansion means contained within the device, one of the wall sections adjacent to the expansion means is fluid-permeable. After the sections are disengaged, fluid enters the device and comes into contact with the active agent contained within the

-3 -

device, thereby dispensing the active agent into the fluid.

Conventional hard gelatin capsules are produced and filled in large numbers using high speed automatic machinery. Such capsules comprise a body and a cap. Normally the cap is pre-fitted to the capsule body during manufacture of the capsule. During filling, the filling machine removes the cap, fills the capsule with pharmaceutical material, and then replaces the cap in a manner such that the cap is locked onto the capsule body. Patent Specification U.S. 3,399,803 discloses a self-locking medicament capsule wherein the body has a groove near its open end, and the cap has a corresponding ridge which snaps into the groove so as to lock the cap and body together. U.S. 4,442,941 discloses a bayonet-type arrangement whereby a raised portion on the cap is engaged into a groove on the body.

European Patent Specification 246804 also discloses a capsule body having a groove near its mouth for the purposes of preventing the capsule distorting from its cylindrical form, which may cause difficulty in fitting the cap onto the capsule body.

A preferred embodiment of the controlled release capsule with which the present invention is concerned (and as disclosed in WO 90/09168) requires that a male hydrogel plug be a close fit within the neck of the female capsule body so that the plug is firmly retained and does not detach prematurely.

-4 -

The hydrogel plug prior to hydration is a fairly rigid material. For these reasons, it may be difficult to insert the tightly fitting hydrogel plug into the mouth of a conventional cylindrical capsule body using high speed machinery. If the body is slightly oval, or the plug and body are not perfectly aligned, there is a danger that the plug will crush or crack the mouth of the capsule body during insertion.

It is an object of the present invention to mitigate this problem.

#### SUMMARY OF THE INVENTION

The present invention provides a controlled release capsule which comprises a male member engaged within a neck portion of a female body; the capsule including a water swellable material which swells so as to disengage the female body upon exposure of the capsule to an aqueous medium; the body comprising a flared mouth portion adjacent the neck portion, the mouth portion having an entrance which is wider than the neck portion and wider than the male member so as to facilitate insertion of the male member into the neck portion.

The flared mouth portion provides a ramped lead-in, so that the male member may be inserted readily into the neck of the female body. Usually, the mouth portion is flared at an angle of 10° to 60° (preferably 15° - 45°) to the line of the capsule. In order to facilitate initial

-5 -

positioning of the male member prior to insertion into the body, the flared mouth may be belled out into a substantially cylindrical entrance portion adjacent the entrance to the body, which is normally of substantially the same diameter as the female body.

Usually, the capsule body and the neck portion thereof are of substantially cylindrical configuration according to conventional practice.

In addition to the flared mouth portion, in one embodiment the neck portion is narrower than the remainder of the body. This enables the flared mouth portion to still be within the overall diameter of the capsule body. A flared mouth portion extending beyond the line of the capsule body may pose problems in handling using high speed filling machinery. Recessing the neck portion in this way may also contribute to the overall strength of the neck portion and minimises splitting. Preferably, the neck portion has a diameter which is 80% to 99% (usually 90 to 98%) of the diameter of the female body. Furthermore, it is preferred that the maximum diameter of the entrance of the flared mouth portion be substantially the same as the diameter of the female body itself.

In another embodiment, the neck portion is wider than the remainder of the body. A step formed where the neck portion meets the remainder of the body may act as a stop which assists insertion of the male member to the correct depth in the neck. The body of this embodiment is also

-6 -

relatively easily demoulded during production.

Although not preferred, the neck portion could be of the same width as the remainder of the body.

Preferably, the capsule body is prepared by conventional capsule forming techniques, which involve dipping a mould pin in a solution of the material (such as gelatin) from which the capsule is to be formed. Spraying could be used instead of dipping. The gelatin is then dried and stripped from the pin. The capsule body may then be trimmed as necessary. The presence of a narrow neck portion which is narrower than the body makes it somewhat more difficult to strip the capsule body from the mould pin, compared to conventional cylindrical capsules. Alternatively, the capsule might be made by other known capsule manufacturing techniques, such as injection moulding of thermoplastic materials.

The walls of the female body may be formed from a wide variety of materials. They may be of homogenous constructions or they may be laminated. Examples of materials suitable for use in the construction of the body include polyethylene, polypropylene, poly(methylmethacrylate), polyvinyl chloride, polystyrene, polyurethanes, polytetrafluoroethylene, nylons, polyformaldehydes, polyesters, cellulose acetate and nitro cellulose.

However, a preferred construction uses an impermeable coating to cover the exterior of a body which has been



-7 -

formed from a water soluble material. The coating may conveniently be formed by dipping the body in a solution of a material which forms a layer which is impermeable to water. Alternatively, the body might be spray-coated. A preferred class of capsule bodies are conventional hard gelatin or starch capsule bodies coated with a solution of polyvinyl chloride or a polyvinyl acetate copolymer or an ethyl cellulose solution.

In a preferred embodiment, the male member is a plug; usually of cylindrical configuration. The plug is formed of the water swellable material, which is preferably a hydrogel. As it absorbs water, the hydrogel plug swells and becomes disengaged from the female body. The hydrogel is preferably a water swellable material as disclosed in patent specification W090/09168.

Usually the neck portion is substantially cylindrical, so as to form a tight fit with the cylindrical male plug.

In another embodiment, the male member is a hollow member closed at one end, whose opposite open end engages within the neck of the female body. A water swellable material is provided within the capsule which serves to disengage the female body after a predetermined time, by forcing the male member and the female body apart as the material swells in the presence of water. The swellable material inside the capsule may be an osmagent or an osmopolymer. Such an arrangement is disclosed in W092/13521. In order to allow water to enter the capsule

-8 -

and to contact the water-swellaable material a portion of the wall of the capsule adjacent thereto is preferably semipermeable; that is to say it is permeable to the passage of water into the device but impermeable to release of other substances from within the capsule.

Another aspect of the invention relates to a process of filling the capsule, which comprises storing caps and bodies separately, filling a body with active material, inserting the male member into the neck of the body, and fitting a cap over the open end of the body.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Embodiments of the present invention will now be described by way of example only in conjunction with the drawings wherein:-

Figure 1 is a cross-sectional elevation of a first embodiment;

Figure 2 is a view from above with the cap removed;

Figure 3 is a partial elevational cross-section of a second embodiment; and

Figure 4 is a partial elevation of a third embodiment with a wider neck.

The capsule shown in Figures 1 and 2 comprises a male member in the form of a plug 2 formed of a hydrogel material, inserted in neck 4 of female body 6. The capsule is closed with a cap 8.

The body 6 comprises a cylindrical main portion 10 and

-9 -

closed end 12. The main body narrows to the neck portion 4 at a shoulder region 5. The neck portion is substantially cylindrical so as to receive the male plug 2 with a close tolerance. The neck portion then flares out to a flared mouth portion 14 which has an entrance 15 of a diameter substantially the same as the diameter of the main body portion 10.

The cylindrical neck portion is advantageously provided with a vent channel 16 shown in dotted lines which extends from the flared mouth portion part way down the neck portion and allows the release of pneumatic pressure from within the capsule body during insertion of the plug. However, the vent channel extends only part way down the neck portion, so that when the plug is fully inserted into the neck, it seals with the lower region of the neck where the vent channel is absent. As shown in Figure 2, a vent channel 16 may be provided on either side of the neck as required.

The male plug 2 is formed of a hydrogel material (such as disclosed in WO 90/09168) and is usually inserted so that the upper end of the plug is level with or below the upper end of the capsule body.

The capsule is then sealed with the cap 8 which is provided with detentes 18 which clip under the rim of the flared mouth portion thereby locking the cap in place.

The cap has a cylindrical skirt portion 9 which extends down to the open end of the cap. The lower end of

-10-

the skirt portion extends downwardly past the shoulder 5 of the body and encloses an upper part of the body with only a small clearance. This helps to stabilise the cap and prevent it tilting from side-to-side. It also allows the cap to be sealed to the body by means of an annular band passing over the junction therebetween.

The cap is formed of a water soluble material, such as gelatin. The capsule body is formed of a water insoluble material, which may be a water insoluble plastics material or may be gelatin coated with a water-impermeable coating.

The capsule body is formed in conventional manner by dipping a mould pin into a gelatin solution and allowing to dry. The gelatin is then coated with a water-impermeable coating (e.g. by dip-coating) after the capsule body has been stripped from the mould pin and trimmed to size. Alternatively, the water-impermeable coating may be applied by spray coating or vapour deposition. The cap 8 is then temporarily fitted over the capsule body such that the detentes 18 do not lock over the rim of the flared mouth portion. The pre-assembled empty capsule is then stored for later filling. During filling, the cap is removed from the capsule body, and a pharmaceutically active material is filled into the capsule body. The hydrogel plug is then fitted into the neck of the body. Finally, the cap is replaced over the end of the capsule body and pushed down so that the

-11-

detentes 18 clip over the rim of the flared mouth portion, thereby locking the cap in place.

However, the preassembly step is not essential. The caps and bodies may be stored separately and fed separately to the filling machine, particularly if precautions are adopted to prevent the caps nesting together and the bodies nesting during storage and feeding in the filling machine. The narrow neck construction shown in Figure 1 helps minimise nesting of the bodies. A flattened cap shape, increased width of the dome of the cap, or increased cap wall thickness helps minimise nesting of caps.

When the capsule is administered to a patient, the aqueous environment in the gastrointestinal tract quickly dissolves the water soluble cap. Water is then absorbed into the hydrogel plug 2, which swells and is expelled from the body after a predetermined time interval (for example 2 to 10 hours). This allows the contents of the capsule to be released into the patient's gastro-intestinal tract.

Figure 3 shows a second embodiment which is similar to the first embodiment, except as regards the shape of the flared mouth portion and the extent of the vent channel. The cap is omitted for simplicity.

Thus, the vent channel 17 extends through the full length of the cylindrical neck portion, so that even when the plug is fully inserted, a total seal is not achieved.

-12-

Such a construction may be easier to demould than the shorter channel shown in the previous embodiment.

The flared mouth portion 14 is belled outwardly, such that the entrance region 15A to the body portion is substantially cylindrical and of a diameter substantially the same as that of the main portion 10. This facilitates location of the plug in the mouth of the body prior to being fully inserted.

Figure 4 shows a third embodiment wherein the cylindrical neck portion 4 is wider than the main body portion 10, and the entrance region 15A is cylindrical. The cap is omitted for simplicity. The step 20 therebetween helps location of the plug 2 so that it is inserted to the correct desired depth in the neck portion 4. Whether the plug is inserted proud of the neck portion, flush with the upper end neck portion, or is recessed below the upper end of the neck portion can affect the time taken to expell the plug. This time will be chosen according to the desired release time of the capsule contents.

-13-

CLAIMS

1. A controlled release capsule which comprises a male member (2) engaged within a neck portion (4) of a female body (6); the capsule including a water swellable material which swells so as to disengage the female body upon exposure of the capsule to an aqueous medium;

the body comprising a flared mouth portion (14) adjacent the neck portion, the mouth portion having an entrance (15) which is wider than the neck portion and wider than the male member so as to facilitate insertion of the male member into the neck portion.

2. A capsule according to claim 1 wherein the neck portion of the female body is substantially cylindrical and is narrower than the remainder of the body.

3. A capsule according to claim 1 wherein the neck portion of the female body is substantially cylindrical and is wider than the remainder of the body.

4. A capsule according to any preceding claim wherein the mouth portion (14) is flared at an angle of  $10^{\circ}$  to  $60^{\circ}$  to the longitudinal direction of the neck portion.

5. A capsule according to any preceding claim wherein the flared mouth is belled out into a substantially cylindrical entrance portion (15).

-14-

6. A capsule according to claim 5 wherein the substantially cylindrical entrance portion is of substantially the same diameter as the female body.

7. A capsule according to any preceding claim wherein the female body and the neck portion are substantially cylindrical and the neck portion has a diameter which is 80 to 99% of the diameter of the female body.

8. A capsule according to any preceding claim wherein the male member is a plug, and the plug is formed of said water swellable material.

9. A capsule according to any preceding claim which further comprises a cap (8) of a water soluble material, the cap having inwardly extending protrusions (18) which clip over the flared mouth portion (14) of the body to lock the cap in place on the body.

10. A capsule according to claim 9 wherein the neck portion of the female body is substantially cylindrical and is narrower than the remainder of the body; and wherein the cap has an open end and a skirt portion (9) adjacent thereto, the skirt portion enclosing a part of said remainder of the body.



1 / 2




FIG. 1




FIG. 2

2 / 2




FIG. 3




FIG. 4

SUBSTITUTE SHEET

## INTERNATIONAL SEARCH REPORT

Inter national Application No  
PCT/GB 93/02270

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 5 A61J3/07

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 5 A61J A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO,A,90 09168 (NATIONAL RESEARCH DEVELOPMENT CORP.) 23 August 1990 cited in the application see abstract	1,4,5,8
Y	FR,A,2 204 541 (ELI LILLY AND COMPANY) 24 May 1974 see claim 1; figures 6,11	1,4,5,8
A	GB,A,2 148 235 (WARNER-LAMBERT) 30 May 1985 see abstract; figure 25	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- \* "A" document defining the general state of the art which is not considered to be of particular relevance
- \* "E" earlier document but published on or after the international filing date
- \* "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \* "O" document referring to an oral disclosure, use, exhibition or other means
- \* "P" document published prior to the international filing date but later than the priority date claimed

\* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\* "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\* "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\* "&" document member of the same patent family

Date of the actual completion of the international search

21 February 1994

Date of mailing of the international search report

21 FEB 1994

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+ 31-70) 340-3016

Authorized officer

Kousouretas, I

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 93/02270

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9009168	23-08-90	AU-B- 629915	15-10-92
		AU-A- 5163290	05-09-90
		EP-A, B 0384646	29-08-90
		EP-A- 0458887	04-12-91
		ES-T- 2043270	16-12-93
		GB-A, B 2230442	24-10-90
		JP-T- 4505004	03-09-92
FR-A-2204541	24-05-74	US-A- 3823843	16-07-74
		AT-B- 338433	25-08-77
		AU-B- 468525	15-01-76
		AU-A- 6079073	27-03-75
		BE-A- 806487	25-04-74
		CA-A- 1017705	20-09-77
		CH-A- 568192	31-10-75
		DE-A- 2353103	09-05-74
		GB-A- 1442121	07-07-76
		JP-C- 1118889	28-10-82
		JP-A- 49080228	02-08-74
		JP-B- 57001265	09-01-82
		NL-A- 7313620	01-05-74
		SE-B- 404906	06-11-78
GB-A-2148235	30-05-85	US-A- 4576284	18-03-86
		BE-A- 900865	19-04-85
		CH-A- 664938	15-04-88
		DE-A- 3438235	30-05-85
		FR-A, B 2555972	07-06-85
		JP-A- 60222060	06-11-85
		US-A- 4738724	19-04-88
		US-A- 4738817	19-04-88